





## MANUFACTURER

HALLDE

## MODEL

RG-100

## PRODUCT DESCRIPTION

Vegetable Preparation Machine, process up to 5 kg/minute.

## ORIGIN

Sweden

		SPECIFICATION			
SPECIFICATION TEXT	Table top vegetable preparation machine with leaning design and half-moon feed cylinder, made to process 5 kg/minute or 20-400 portions/day. Machine has acetal pusher plate and a tube feeder of 56 mm in diameter. 1.65 litre feed cylinder. Cutting tools are made of stainless steel/aluminium/acetal with removable knifes/plates and are 185 mm in diameter. Motor rotate the cutting blade clockwise and direct without intermediate belts.				
FUNCTION	Machine for slicing, dicing, shredding, grating and cutting julienne. Processes fruit, vegetables, dry bread, cheese, nuts, mushrooms, etc.				
CAPACITY	Up to 400 portions/day and up to 5 kg/minute.  1.65 liter feed cylinder, 56 mm tube feeder for elongated products.				
MATERIAL	Machine base and feed cylinder: aluminium alloy. Pusher plate: acetal Cutting tools: stainless steel/aluminium/fiberglass reinforced polyaminde. Ejector plate: acetal.				
MOTOR	0.25 kW. One-speed (350 rpm) 100 V, 1-phase, 50/60 Hz.   110-120 V, 1-phase, 60 Hz 220-240 V, 1-phase, 50/60 Hz.   380-420 V, 3-phase, 50/60 Hz. Thermal protection, Planetary gearing.				
POWER SUPPLY	Earthed, single phase, 10 A/three phase, 10A slow-blow. Fuse: 10 A delayed action fuse.				
STANDARDS	EN 1678+A1:2010. NSF/ANSI Standard 8.				
RECOMMENDED CUTTING TOOL PACKAGES	INCLUDING				NET WEIGHT
	<ul> <li>4-pack Cutting Tools</li> <li>Slicer 1.5 mm</li> <li>Slicer 4 mm</li> <li>Grater/Shredder 2 mm</li> <li>Grater/Shredder 4 mm</li> </ul>				2 kg
	7-pack Cutting Tools     Slicer 1.5 mm				3,5 kg
WEIGHT/VOLUME	CONTENT	NET WEIGHT	PACKAGES	FREIGHT WEIGHT	FREIGHT VOLUME
	RG-100 Machine	16.4 kg	1	16,7 kg	0.077 m <sup>3</sup>
	Container Trolley incl. GN 1/1 container	9 kg	1	12.5 kg	0.15 m <sup>3</sup>
	Machine Table incl. GN 1/1 container	13,25 kg	1	14,5 kg	0,8 m³
SAFETY	2014/30/EU, 2014/35/EU, 2006/42/EG, 2011/65/EU, no 10/2011				
DIRECTIVE AND REGULATION	CE approved. Two safety switches, machine safety: IP44, push buttons safety: IP65.				

