

UPster PF 600

Execution for: Australia

Country of production: China

Utensil washing machine

3-phase current: 3N PE 400V 50Hz

Fresh water line: Soft warm water 0-3°dH



Sample illustration

Technical data

Rack capacity/h (theoretical)	30 / 15 / 10 racks/h
Programme cycle *	120 / 240 / 360 s
Rack dimension	670 x 630 mm
Entry height	600 mm
Dimensions (W x Hmin x D)	870 x 1600 x 760 mm
Electrical feeding cable	3-phase current 3N PE 400V 50Hz* Total connected load: 11.2 kW max. rated current: 18.5 A
Local fuse protection	20 A
Protection class of the machine	IP X4
Equipment	MIKE control Infrared interface for wireless communication Drain pump Boiler safety device Automatic self-cleaning when tank is drained
Fresh water line	Air gap 'AA' in accordance with EN 1717 with booster pump
Fresh water supply	Minimum flow pressure 60 kPa / 0.6 bar in front of solenoid valve Maximum pressure 500 kPa / 5.0 bar Max. supply water temperature 60 °C
Flow rate	4 l/min
Final rinse water quantity	4 liters/cycle
Boiler	Contents: 10.5 l Heater: 9.00 kW Temperature: 83 °C Tank / boiler interlocked
Wash tank	Filling: 60 l Heater: 6.00 kW Temperature: 60 °C

Technical Information

Wash pump	Performance: 2.00 kW
Dosing of rinse aid	Hose pump (24 V) with time control and suction lance
Detergent dosage	Hose pump (24 V) with time control and suction lance
Material	Cladding: 1.4301 Wash tank: 1.4301 Boiler: 1.4404
Heat emission	for 15 programme cycles/h total: 2.8 kW perceptible: 1.9 kW latent: 0.9 kW
Ventilation flow rate	710 m³/h
Steam emission	1.3 kg/h
Sound level	68 dB(A)
Net / gross weight	165.0 kg / 190.0 kg (standard packaging)
Packaging dimensions (W x H x D)	1050 x 1750 x 1000 mm (standard packaging)

***Note:**

Electrical equipment suitable for supply voltage:
3N PE 400 V 50 HZ (3N PE 380-415 V 50 Hz)
1N PE 230 V 50 HZ (1N PE 220-240 V 50 Hz)